



M6FT4EL/M6FT4ER



M6FT6EL/M6FT6ELR

**DESCRIZIONE PRODOTTO / PRODUCT DESCRIPTION**

Frytop elettrico con piastra liscia, rigata o mista (liscia/rigata). Piano spessore 10/10. Il convogliatore di raccolta grassi e residui è posto davanti alla piastra. La piastra è riscaldata a mezzo di speciali resistenze corazzate. Controllo della temperatura ottenuto per mezzo di un termostato con regolazione progressiva della potenza erogata. La sicurezza è garantita da un termostato di sicurezza. Struttura costruita in acciaio inox.

*Electric griddle with smooth plate, grooved or mixed (smooth/grooved). Top thickness 10/10. The collection drawer for fats and residues is located front the plate. The plate is heated by special armored elements. Temperature control made by thermostat gradual regulation of the power supplied. The safety is guaranteed by a safety thermostat. Framework made in stainless steel.*

**CARATTERISTICHE TECNICHE**

## TECHNICAL CHARACTERISTICS

	M6FT4EL/M6FT4ER	M6FT6EL/M6FT6ELR
Dimensioni / Dimensions	400 x 600 x 270 mm	600 x 600 x 270 mm
Peso netto / Net weight	26 Kg	34 Kg
Riciclabilità % del peso apparecchio / Recyclability % weight of appliance	98%	98%
Tensione / Voltage	380/415V 3N	380/415V 3N
Ampere / Amperes	5,2 A	6,9 A
Frequenza / Frequency	50/60 Hz	50/60 Hz
Consumo d'energia elettrica / Electric energy consumption	3,6 kW	4,8 kW
Indice di protezione all'acqua / Water ingress protection rating	IPX4	IPX4
Piastra fry-top / Griddle plate	15,6 dm <sup>2</sup>	24,3 dm <sup>2</sup>
Dimensioni imballo / Package dimensions	430 x 660 x 430 mm	630 x 660 x 430 mm
Peso lordo / Gross weight	27 Kg	36Kg
Volume / Volume	0,12 m <sup>3</sup>	0,18 m <sup>3</sup>

EMME 6


**EMME**

**FRY-TOP ELETTRICO**







ELECTRIC GRIDDLE



M6FT4EL  
M6FT4ER



M6FT6EL  
M6FT6ELR



**PIASTRA LISCIA**  
**SMOOTH PLATE**



**PIASTRA LISCIA/RIGATA**  
**SMOOTH/GROOVED PLATE**